according to Regulation (EC) No 1907/2006

# JG600 STERILIT I Oil spray

Revision date: 20.02.2024 Product code: 00250-0001 Page 1 of 10

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

JG600 STERILIT I Oil spray

UFI: Q8RA-E65F-E70F-5X9H

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Preservative agent

### 1.3. Details of the supplier of the safety data sheet

AESCULAP AG Company name: Street: Am AESCULAP-Platz Place: D-78532 Tuttlingen/Donau

Telephone: +49 (0) 74 61 95-0 Telefax: +49 (0) 74 61 95-2600

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a) 1.4. Emergency telephone number:

Public Poisons Information Line: +353 (0) 1 809 2166 (8am-10pm 7 days a

week)

### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

## Regulation (EC) No 1272/2008

Aerosol 1; H222-H229

Full text of hazard statements: see SECTION 16.

# 2.2. Label elements

### Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



## **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

## **Precautionary statements**

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

In use, may form flammable/explosive vapour-air mixture.

according to Regulation (EC) No 1907/2006

# JG600 STERILIT I Oil spray

Revision date: 20.02.2024 Product code: 00250-0001 Page 2 of 10

### **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

### **Chemical characterization**

Aerosol with preparation of special oil

### **Hazardous components**

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (Regulation (EC) No 1272/2008)				
106-97-8	Butane			< 100 %	
	203-448-7	601-004-00-0	01-2119474691-32		
	Flam. Gas 1, Press. Gas (Comp.); H220 H280				

Full text of H and EUH statements: see section 16.

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### After inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

## After contact with skin

Wash with water and soap as a precaution.

Consult a doctor if skin irritation persists.

### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

If eye irritation persists, consult a specialist.

# After ingestion

Do not induce vomiting.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

# 4.2. Most important symptoms and effects, both acute and delayed

Attention. Beware, danger of aspiration.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Inhalation of vapours in high concentration can cause narcotic effects.

Evaporative cooling effect during use.

May cause eye/skin irritation.

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

## **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

# Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

## Unsuitable extinguishing media

Full water jet.

according to Regulation (EC) No 1907/2006

# JG600 STERILIT I Oil spray

Revision date: 20.02.2024 Product code: 00250-0001 Page 3 of 10

## 5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide and carbon dioxide

### 5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

### Additional information

Cool containers at risk with water spray jet. Heating will cause pressure rise with risk of bursting.

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### General advice

Ensure adequate ventilation.

Remove all sources of ignition.

Keep away noninvolved persons.

### For non-emergency personnel

Do not breath vapours or spray mist.

Avoid contact with skin, eyes and clothing.

### For emergency responders

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/aerosol.

## 6.2. Environmental precautions

Do not discharge product unmonitored into the environment.

### 6.3. Methods and material for containment and cleaning up

### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

### For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Informations for disposal look up chapter 13.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

## Advice on safe handling

Ensure adequate ventilation.

Avoid contact with skin, eyes and clothing.

Do not breathe aerosol

### Advice on protection against fire and explosion

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Without adequate ventilation formation of explosive mixtures may be possible.

# Advice on general occupational hygiene

Do not breathe aerosol

according to Regulation (EC) No 1907/2006

# JG600 STERILIT I Oil spray

Revision date: 20.02.2024 Product code: 00250-0001 Page 4 of 10

Wash hands before breaks and at the end of workday.

When using do not eat, drink or smoke.

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Store at ambient temperature in a well-ventilated place. Keep container tightly closed.

### Hints on joint storage

Incompatible with oxidizing agents.

### Further information on storage conditions

Keep away from food and drink.

### 7.3. Specific end use(s)

Preservative agent

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

## Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
106-97-8	Butane, all isomers - n-butane	1000	-		STEL (15 min)	

### 8.2. Exposure controls

## Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

### Individual protection measures, such as personal protective equipment

## Eye/face protection

If used properly, no need to wear eye protection.

Avoid contact with the eyes.

### Hand protection

If used properly, protective gloves are normally not required.

Avoid contact with the skin.

### Respiratory protection

No personal respiratory protective equipment normally required.

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type AX) (EN 14387).

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: Colourless
Odour: Characteristic

### Test method

### Changes in the physical state

Melting point/freezing point:  $-138,3 \ ^{\circ}C \ ^{*})$  Boiling point or initial boiling point and  $-0,5 \ ^{\circ}C \ ^{*})$  boiling range:

Sublimation point:

n.a.

Softening point:

n.a.

- 87 °C \*)

**Flammability** 

according to Regulation (EC) No 1907/2006

JG600 STERILIT I Oil spray					
Revision date: 20.02.2024	Product code: 00250-0001	Page 5 of 10			
Solid/liquid:	n.a.				
Explosive properties					

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits: 1,5 vol. % \*) Upper explosion limits: 8,5 vol. % \*) 365 °C \*) Auto-ignition temperature:

Self-ignition temperature Solid: n.a. Gas: n.a. Decomposition temperature: pH-Value: Not detectable by analysis Viscosity / dynamic: Viscosity / kinematic: n.a. Flow time: n.a. Water solubility: 0,0535 g/L \*)

(at 20 °C) Solubility in other solvents

n. d.

Partition coefficient n-octanol/water: n. d.

Vapour pressure: 2200 hPa \*)

(at 20 °C)

Density (at 20 °C): 0,58 g/cm<sup>3</sup> \*) Bulk density: n.a. Relative vapour density: n. d.

# 9.2. Other information

## Information with regard to physical hazard classes

Sustaining combustion: Sustaining combustion

Oxidizing properties Not oxidising.

### Other safety characteristics

Evaporation rate: n. d.

## **Further Information**

\*) Butane

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No decomposition if stored and applied as directed.

## 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Reactions with oxidising agents.

### 10.4. Conditions to avoid

Fire or intense heat may cause violent ruptur of packages.

## 10.5. Incompatible materials

Strong oxidizing agents

according to Regulation (EC) No 1907/2006

# JG600 STERILIT I Oil spray

Revision date: 20.02.2024 Product code: 00250-0001 Page 6 of 10

### 10.6. Hazardous decomposition products

No hazardous decomposition products known.

Fire may produce:

carbon monoxide and carbon dioxide

# **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Based on available data, the classification criteria are not met.

No toxical dates available.

### **ATEmix** calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

### Irritation and corrosivity

Based on available data, the classification criteria are not met.

### Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

## Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

## **Practical experience**

Evaporative cooling effect during use.

## 11.2. Information on other hazards

# **Endocrine disrupting properties**

No data available

### Other information

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Inhalation of vapours in high concentration can cause narcotic effects.

Evaporative cooling effect during use.

May cause eye/skin irritation.

May cause irritation of the mucous membranes.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecological dates are not available.

# 12.2. Persistence and degradability

No data available

# 12.3. Bioaccumulative potential

No data available

## 12.4. Mobility in soil

No data available

Print date: 29.02.2024

# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## JG600 STERILIT I Oil spray

Revision date: 20.02.2024 Product code: 00250-0001 Page 7 of 10

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No data available

### **Further information**

Do not flush into surface water or sanitary sewer system.

Ecological injuries are not known or expected under normal use.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

### **Disposal recommendations**

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

### List of Wastes Code - residues/unused products

150111 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers; hazardous waste

### Contaminated packaging

Offer empty spray cans to an established disposal company

# **SECTION 14: Transport information**

# Land transport (ADR/RID)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es): 2
14.4. Packing group: Hazard label: 2.1



Classification code: 5F

Limited quantity: 1 L / 30 kg
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code:

according to Regulation (EC) No 1907/2006

Revision date: 20.02.2024 Product code: 00250-0001 Page 8 of 10

Limited quantity: 1 L / 30 kg Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Marine pollutant: No

Limited quantity: 1000 mL / 30 kg

Excepted quantity: E0 F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40

Directive 2004/42/EC on VOC in 98 %

paints and varnishes:

Information according to Directive

2012/18/EU (SEVESO III):

P3a FLAMMABLE AEROSOLS

National regulatory information

according to Regulation (EC) No 1907/2006

## JG600 STERILIT I Oil spray

Revision date: 20.02.2024 Product code: 00250-0001 Page 9 of 10

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): -- non-hazardous to water

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### **SECTION 16: Other information**

### Changes

This data sheet contains changes from the previous version in section(s): 9.

### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

## Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure: may explode if heated.

### **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable: n.d. = not determined)"

according to Regulation (EC) No 1907/2006

# JG600 STERILIT I Oil spray

Revision date: 20.02.2024 Product code: 00250-0001 Page 10 of 10

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)